## OKUMURA et al Serial No. (to be assigned)

- 2. The catalyst for purifying exhaust gas as defined in claim 1, wherein iridium is deposited on a support containing sulfur.
- 3. The catalyst for purifying exhaust gas as defined in claim 1, wherein sulfur is provided as a sulfate.
  - 4. A catalyst for purifying exhaust gas comprising:
- a fire-resistant inorganic compound having at least one element selected from the group consisting of platinum, palladium and rhodium deposited thereon; and a metallic sulfate having iridium deposited thereon.
  - 10. (Amended) A catalyst for purifying exhaust gas comprising:

iridium, a rare-earth metal oxide, and sulfur; and

at least one element selected from a group consisting of calcium, strontium and barium, as catalyst active substances,

wherein the iridium forms a complex oxide with said at least one element.

11. The catalyst for purifying exhaust gas as defined in claim 10, wherein iridium forms a complex oxide with said at least one element selected from the group of said elements.

M

- 12. The catalyst for purifying exhaust gas as defined in claim 10, wherein iridium is deposited on a support containing sulfur.
- 13. The catalyst for purifying exhaust gas as defined in claim 10, further comprising a fire-resistant inorganic compound.
- 14. (Amended) A catalyst for purifying exhaust gas comprising iridium, a rareearth metal and sulfur, and

wherein the fare-earth metal is contained as an oxide containing at least one element selected from a group consisting of cerium, lanthanum, yttrium, neodymium and praseodymium.

- 15. The catalyst for purifying exhaust gas as defined in claim 14, wherein the rareearth metal is contained as an oxide containing at least one element selected from the group consisting of cerium, lanthanum, yttrium, neodymium and praseodymium.
- 16. (Amended) A catalyst for purifying exhaust gas comprising iridium, a rare-earth metal and sulfur, wherein the rare-earth metal is contained as a composite oxide containing at least one element selected from a group consisting of cerium, lanthanum, yttrium, neodymium and praseodymium, and at least one element selected from a group consisting of manganese, iron, cobalt, nickel, copper and zinc.

- 17. The catalyst for purifying exhaust gas as defined in claim 14, further comprising at least one element selected from the group consisting of tin, gallium, germanium and silicon.
- 18. (Amended) An exhaust-gas purifying process comprising the steps of:

  preparing a catalyst for purifying exhaust gas by forming the catalyst of
  iridium, a rare earth metal oxide, and sulfur; and at least one element selected from a
  group consisting of calcium, strontium and barium, as catalyst active substances, wherein
  the iridium forms a complex oxide with said at least one element;

setting an exhaust-gas/temperature in a range of 200°C to 700°C at an inlet to the catalyst for purifying the exhaust gas; and

directing the exhaust gas from an internal combustion engine through the catalyst for purifying the exhaust gas so as to reduce nitrogen oxides in the exhaust gas.

19. (Amended) An exhaust-gas purifying process comprising the steps of:

preparing a catalyst for purifying exhaust gas by forming the catalyst of
iridium, a rare earth metal oxide, and sulfur; and at least one element selected from a
group consisting of calcium, strontium and barium, as catalyst active substances, wherein
the iridium forms a complex oxide with said at least one element;

## OKUMURA et al Serial No. (to be assigned)

setting an exhaust-gas temperature in a range of 200°C to 700°C at an inlet to the catalyst for purifying the exhaust gas, and

directing the exhaust gas from an internal combustion engine through the catalyst for purifying the exhaust gas so as to reduce hydrocarbons, carbon monoxide and nitrogen oxides in the exhaust gas from the internal combustion engine.

20 24 A

An exhaust-gas purifying process comprising the steps of:

preparing a catalyst comprising iridium, a rare-earth metal and sulfur, wherein the rare-earth metal is an oxide containing at least one element selected from a group consisting of cerium, lanthanum, yttrium, neodymium and praseodymium;

setting an exhaust-gas temperature in a range of 200°C to 700°C at an inlet to the catalyst for purifying exhaust gas; and

directing an exhaust gas from an internal combustion engine through the catalyst to purify the exhaust gas and reduce nitrogen oxides in the exhaust gas.

25. An exhaust-gas purifying process comprising the steps of:

preparing a catalyst comprising iridium, a rare-earth metal and sulfur, wherein the rare-earth metal is an oxide containing at least one element selected from a group consisting of cerium, lanthanum, yttrium, neodymium and praseodymium;

## OKUMURA et al Serial No. (to be assigned)

nickel, copper and zinc;

setting an exhaust-gas temperature in a range of 200°C to 700°C at an inlet to the catalyst; and

directing an exhaust gas from an internal combustion engine to pass through the catalyst for purifying exhaust gas so as to reduce hydrocarbons, carbon monoxide and nitrogen oxides in the exhaust gas from the internal combustion engine.

An exhaust-gas purifying process comprising the steps of:

preparing a datalyst comprising iridium, a rare-earth metal and sulfur, wherein the rare-earth metal is a composite oxide containing at least one element selected from a group consisting of cerium, lanthanum, yttrium, neodymium and praseodymium, and at least one element selected from a group consisting of manganese, iron, cobalt,

setting an exhaust-gas temperature in a range of 200°C to 700°C at an inlet to the catalyst for purifying exhaust gas; and

directing an exhaust gas from an internal combustion engine through the catalyst to purify the exhaust gas and reduce nitrogen oxides in the exhaust gas.

27. An exhaust-gas purifying process comprising the steps of:

preparing a catalyst comprising iridium, a rare-earth metal and sulfur, wherein the rare-earth metal is a composite oxide containing at least one element selected